

MultiSync® C551 LCD 55" Value Large Format Display

Datasheet





Seamless integration for great visual performance

Its thin bezel and super slim design perfectly complements today's modern surroundings whilst multiple display inputs support flexibility and freedom. With fixing points conveniently located on the back of the screen, external equipment can be attached with seamless simplicity. Reasonable brightness levels offer visibility in controlled light surroundings. The professional haze filter is allowing excellent readability. Landscape and portrait capability matches the needs of both corporate huddle spaces and retail signage applications. With a built-in media player, the NEC C Series runs content directly from a USB drive or microSD card as a standalone solution but can also download contents via network. Futureproof connectivity handles input from multiple sources. Don't let technology impact design – get seamless integration with the NEC C Series!

Benefits

Impressive FullHD LCD technology – eye-pleasing black levels and impressive contrast ratios for ergonomic viewing and less fatigue in conferencing scenarios.

Modern and slim design – robust yet elegant allowing for an unobtrusive integration into any application and environment.

All-in-one Signage solution integrated – the integrated mediaplayer for simple signage use supports easy content playback and management.

Mission-critical 24/7 ready operation – the meticulous selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.

Ease of use and operation – Smart installation, operation and maintenance functionality ensures accurate performance over the entire lifetime of the display saving time, effort and resources.

Free Download of Multi-Display Management Software – with NaViSet Administrator 2 you can manage all your connected display devices from a centralised location.

Dun	44	Inform	-4:

Product Name	MultiSync® C551
Product Group	LCD 55" Value Large Format Display
Order Code	60004238

Display

Panel Technology	AMVA3 with Edge LED backlights
Active Screen Area (W x H) [mm]	1,210 x 680
Screen Size [inch/cm]	55 / 138.8
Brightness [cd/m²]	400, 280 Eco (shipment setting)
Contrast Ratio (typ.)	4000:1
Viewing Angle [°]	178 / 178 (at contrat ratio > 10:1)
Colour Depth [bn]	1.073 (10bit)
Response Time (typ.) [ms]	8 (grey-to-grey)
Haze Level [%]	Pro (44)
Supported Orientation	Face Down; Face Up; Landscape; Portrait

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 91.1 (analog and digital)
Vertical Frequency [Hz]	24 - 85

Resolution

Native Resolution	1920 x 1080
Supported Resolutions	1920 x 1200; 1920 x 1080; 1680 x 1050; 1600 x 1200; 1440 x 900; 1400 x 1050; 1360 x 768; 1280 x 1024;
	1280 x 960; 1280 x 800; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600

Connectivity

1 x VGA
1 x DisplayPort (with HDCP); 3 x HDMI (with HDCP)
2 x 3,5 mm jack
1 x DisplayPort; 3 x HDMI
1 x LAN 100Mbit; 1 x Remote Control (3.5 mm jack); 1 x RS232
1 x microSD (MediaPlayer); 1 x USB 2.0 (MediaPlayer)
1 x 3,5 mm jack
remote control wire (3,5mm jack)

Sensors

Ambient Light Sensor	Integrated, triggered actions programmable
Temperature Sensor	Integrated, 3 sensors, triggered actions programmable

Electrical

Power Consumption [W]	75 shipping
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)
Power Management	VESA DPMS

Environmental Conditions

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	20 to 80

Mechanical

1,238 x 709 x 45
18.8
12.4 (left and right); 12.4 (top and bottom)
300 x 300 (FDMI); 4 holes; M6
IP5X (front); IP2X (back)

Additional Features

Special Characteristics	Ambient Light Sensor; AMX NetLinx Support; ASCII Control Commands; Automated Email Alert; CEC	
	Support; Crestron Connected Support; Crestron RoomView Support; Display Browser Control; Emergency	
	Notification; Full System Scheduler; KeyGuide; MediaPlayer with Browser Control; NaViSet Administrator 2;	
	OmniColor Control; OSD rotation for portrait mode; PJLink Support; Powered USB-Port; Removable Logo;	
	Secure Mode Operation; Slim LED Indicator; SNMP Support; TileMatrix (10 x 10); User readable log function	
Colour Versions	Black Front Bezel, Black Back Cabinet	
Safety and Ergonomics	C-tick; CE; EMC Class B; FCC; PSB; RoHS; TÜV GS; UL/C-UL or CSA; VCCI	
Audio	Integrated Speakers (10 W + 10 W)	
Shipping Content	CD-ROM (User Guides/Manuals); Display; Power Cable; Remote Control; VGA cable	
Warranty	3 years warranty incl. backlight; additional services available	
Operating Hours	24/7	

Available Options

Accessories	Feet (ST-401); Trolley (PDMHM-L); Wall mount (PDW S 32-55 L and P, PD02W T M L, PD03W T M P)
-------------	--

MediaPlaver

Supported Image Formats	JPG (baseline, progressive, RGB, CMYK); max. resolution 5000 x 5000; PNG (interlace, alpha channel); max. resolution 4000 x 4000
Supported Video Formats	MP4 / MOV / FLV (video H.264, audio MP3, AAC); max. resolution 1080p at 30 Hz, 1080i at 60 Hz; MPG (video mpeg1/2, audio mpeg audio layer2/3, AAC-LC); MP @ ML, MP @ HL; WMV (video H.264, wmv advanced L3, wmv simple / main, audio mp3 wmv std); max. resolution 1080p at 30 Hz, 1080i at 60 Hz
Supported Audio Formats	MP3 (MP3); max. bit-rate 320 kBit/s; WAV (LPCM); max. 48 kHz sampling
Supported File Storage / File System	MicroSDHC / FAT16, FAT32; USB 2.0 / FAT16, FAT32

Green Features

Energy Efficiency	Ambient light sensor; Annual energy consumption: 120 kWh (based on 4 operating hours per day); Carbon savings meter; Energy efficiency class: A+
Ecological Materials	Manuals on CD; Optional feet
Ecological Standards	EnergyStar 7.0











This document is $\hbox{@\,}2017$ NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 12.10.2017